


- 3/8" Steel chassis – Hot-dipped galvanized
- UV inhibitors to protect from the effects of the sun
- Permanently lubricated and sealed bearings
- 1" hardened steel shaft
- Roller secured to shaft with nylon locknut

PRODUCT DESCRIPTION

- No. 5200Roll gate track roller with bracket assembly
- No. 53502" Square pipe roller – 4" Round post
2200 lb. load rating – nylon
- No. 5350-3S...2" Square pipe roller – 3" Square post
2200 lb. load rating – nylon
- No. 5350-4S...2" Square pipe roller – 4" Square post
2200 lb. load rating – nylon
- No. 5350-6S...2" Square pipe roller – 6" Square post
3500 lb. load rating – nylon – double bearing
- No. 55002" O.D. Frame size – 4" O.D. Round Post
1000 lb. load rating – UHMW
- No. 56582½" O.D. Frame size – 6½" O.D. post
3500 lb. load rating – nylon – double bearing
- No. 58002½" O.D. Frame size – 4" O.D. post
2200 lb. load rating – nylon
- No. 5800-3 ...2½" O.D. Frame Size – 3" O.D. Round post

STEALTH SERIES ● CANTILEVER ROLLERS		 1-800-888-9768 www.dacindustries.com
JOB / PROJECT	DATE	
		_____ OF _____